






**Quad Flat No-Lead Plastic Package (QFN)  
Micro Lead Frame Plastic Package (MLFP)**

**L64.9x9-S**

**64 LEAD QUAD FLAT NO-LEAD PLASTIC PACKAGE**



SYMBOL	MILLIMETERS			NOTES
	MIN	NOMINAL	MAX	
A	0.80	0.85	0.90	-
A1	-	-	0.05	-
A2	0.60	0.65	0.70	-
A3	0.25 REF			-
b	0.18	0.23	0.30	5, 8
D	9.00 BSC			-
D1	8.75 BSC			-
D2	3.70	3.80	3.90	7, 8
E	9.00 BSC			-
E1	8.75 BSC			-
E2	3.70	3.80	3.90	7, 8
e	0.50 BSC			-
L	0.30	0.40	0.50	8
L1	-	-	0.15	9
N	64			2
Nd	16			3
Ne	16			3
P	-	-	0.50	-
θ	10	11	12	-

Rev. 1 2/09

NOTES:

1. Dimensioning and tolerancing conform to ASME Y14.5-1994.
2. N is the number of terminals.
3. Nd and Ne refer to the number of terminals on each D and E.
4. All dimensions are in millimeters. Angles are in degrees.
5. Dimension b applies to the metallized terminal and is measured between 0.15mm and 0.30mm from the terminal tip.
6. The configuration of the pin #1 identifier is optional, but must be located within the zone indicated. The pin #1 identifier may be either a mold or mark feature.
7. Dimensions D2 and E2 are for the exposed pads which provide improved electrical and thermal performance.
8. Nominal dimensions are provided to assist with PCB Land Pattern Design efforts, see Intersil Technical Brief TB389.
9. Depending on the method of lead termination at the edge of the package, a maximum 0.15mm pull back (L1) maybe present. L minus L1 to be equal to or greater than 0.3mm.